arXiv:1602.08689v2 [physics.flu-dyn] 24 May 2016

Temperature jump in second Stokes' problem by nonlinear analysis

A. V. Latyshev[1] **and A. A. Yushkanov**[2]

Faculty of Physics and Mathematics,
Moscow State Regional University, 105005,
Moscow, Radio str., 10A

The second Stokes problem about behavior of the viscous fluid (matter) filling half-space is considered. A flat surface limiting half-space makes harmonious oscillations in the eigen plane. The equations of mechanics of the continuous environment are used. It is shown, that in considered process there is the temperature difference between temperature of a surface and temperature environments far from a surface. Usually similar difference is called as temperature jump. The method of small parameter is applied. Temperature jump in the second approach is found out.

Key words: second Stokes problem, field of velocities, temperature jump.

PACS numbers: 05.20.Dd Kinetic theory, 47.45.-n Rarefied gas dynamics, 51. Physics of gases, 51.10.+y Kinetic and transport theory of gases.

For the first time the problem about behavior of gas over a wall oscillating in the eigen plane, it is considered by G. G. Stokes [1]. It often called as the second Stokes' problem.

Problem about behavior of the viscous fluid matter over a moving surface in the last years the steadfast attention attracts [2] – [10]. It is connected with development of modern technologies, in particular, nano-technologies.

Recently the problem about fluctuations of a flat surface and for a case non-Newton liquids [2] is studied.

[1] *avlatyshev@mail.ru*
[2] *yushkanov@inbox.ru*

For a various sort of currents of environment the second Stokes' problem was studied in [3], in [4] questions of a friction and warmth allocation, in [5] were investigated every possible appendices of this problem were considered.

In [6] the example of practical application of the oscillatory The system similar to the considered problem, in area нанотехнологий is considered.

In experiments [7] the stream of gas created by the mechanical resonator at various frequencies of fluctuation was studied. For a case of low frequencies the problem on the basis of the equation of Navier—Stokes' is solved. In case of any speeds of fluctuations of a surface were used numerical methods on the basis of the kinetic equation with integral of collisions in the form of BGK (Bhatnagar, Gross and Krook).

In gases with use of the kinetic equations the second problem Стокса in works [7] – [12] was considered.

In work [8] numerical methods of the decision of second Stokes' problem were applied, and in works [9] and [10] for the problem decision were used approximations methods. Second Stokes' problem in electromagnetic fields was it is investigated in [13].

In our works [11] and [12] the second Stokes' problem analytically for rarefied gas is solved. The model Boltzmann' kinetic equation with integral of collisions type BGK thus was used. In [11] the problem with diffusion boundary conditions was solved. It is shown, that results of works [8] and [10] are rather close with the results received from the analytical decision [11]. Results from [11] on a case of boundary Cercignani' conditions in [12] have been generalized.

In the present work we find jump of temperature by which process of generating of a sound wave by a surface oscillating harmoniously in the plane is accompanied.

The method of small parameter is applied. Temperature jump is found out in the second approximation.

Let the viscous fluid matter fills half-space $x > 0$ over the flat firm surface laying in a plane $x = 0$. The surface (y, z) makes harmonious oscillations along an axis y under the law $u_s(t) = U_0 e^{-i\omega t}$. It is required to find jump

of temperature, formed between temperature of the wall and temperature of viscous fluid matter far from a wall.

We take system of the equations of the continuous environment (see, for example [14])

$$\rho\big(\frac{\partial V_i}{\partial t}+v_k\frac{\partial V_i}{\partial x_k}\big)+\frac{\partial p}{\partial x_i}=$$

$$=\frac{\partial}{\partial x_k}\Big\{\eta\big(\frac{\partial V_k}{\partial x_i}+\frac{\partial V_i}{\partial x_k}-\frac{2}{3}\delta_{ik}\mathrm{div}\mathbf{V}\big)\Big\}+\frac{\partial}{\partial x_i}\zeta(\mathrm{div}\mathbf{V}), \tag{1}$$

$$\rho T\big(\frac{\partial s}{\partial t}+\mathbf{V}\nabla s\big)=$$

$$=\mathrm{div}(\varkappa\nabla T)+\frac{\eta}{2}\Big(\frac{\partial V_k}{\partial x_i}+\frac{\partial V_i}{\partial x_k}-\frac{2}{3}\delta_{ik}\mathrm{div}\mathbf{V}\Big)^2+\zeta\big(\mathrm{div}\mathbf{V}\big)^2, \tag{2}$$

and

$$\frac{\partial\rho}{\partial t}+\mathrm{div}(\rho\mathbf{V})=0. \tag{3}$$

Here s is the entropy of a mass unit of environment, $\mathbf{V}=(u,v)$ is the velocity of fluid matter, $u=u_y(t,x)$, $v=u_x(t,x)$ are components of velocity of fluid matter, η is the dynamical viscosity of fluid, ζ is the second viscosity of fluid, $\varkappa$ is the heat conductivity coefficient, T is the temperature of fluid matter, c_p is the thermal capacity at constant pressure, p is the pressure in fluid matter. For gases $p=\rho k_BT/m$, k_B is the Boltzmann constant, m is the mass of molecule, ρ is the density of fluid matter.

On repeating indexes summation is meant.

Let us calculate the quantity

$$\Big(\frac{\partial V_k}{\partial x_i}+\frac{\partial V_i}{\partial x_k}-\frac{2}{3}\delta_{ik}\mathrm{div}\mathbf{V}\Big)^2=$$

$$=\Big(\frac{\partial V_k}{\partial x_i}+\frac{\partial V_i}{\partial x_k}\Big)^2-\frac{4}{3}\delta_{ik}\mathrm{div}\mathbf{V}\Big(\frac{\partial V_k}{\partial x_i}+\frac{\partial V_i}{\partial x_k}\Big)+\frac{4}{9}\delta_{ik}^2(\mathrm{div}\mathbf{V})^2=$$

$$=\Big(\frac{\partial V_1}{\partial x_2}+\frac{\partial V_2}{\partial x_1}\Big)^2+\Big(\frac{\partial V_2}{\partial x_1}+\frac{\partial V_1}{\partial x_2}\Big)^2+\Big(\frac{\partial V_1}{\partial x_1}+\frac{\partial V_1}{\partial x_1}\Big)^2-$$

$$-\frac{4}{3}\Big(\frac{\partial V_1}{\partial x_1}\Big)\Big(\frac{\partial V_1}{\partial x_1}+\frac{\partial V_1}{\partial x_1}\Big)+\frac{4}{9}(\delta_{11}+\delta_{22}+\delta_{33})\Big(\frac{\partial V_1}{\partial x_1}\Big)^2=$$

$$= 2\Big(\frac{\partial V_2}{\partial x_1}\Big)^2 + 4\Big(\frac{\partial V_1}{\partial x_1}\Big)^2 - \frac{8}{3}\Big(\frac{\partial V_1}{\partial x_1}\Big)^2 + \frac{4}{3}\Big(\frac{\partial V_1}{\partial x_1}\Big)^2 =$$

$$= 2\Big(\frac{\partial u}{\partial x}\Big)^2 + \frac{8}{3}\Big(\frac{\partial v}{\partial x}\Big)^2.$$

The boundary condition is formulated from the condition, that the wall makes, as already it was specified, harmonious oscillations. Hence, the boundary condition on the wall has the following form

$$u(t,0) = U_0 \cos \omega t = \mathrm{Re}\,(U_0 e^{-i\omega t}). \tag{4}$$

In boundary conditions (4) possibility of sliding of gas along a surface is neglected. It means, that corresponding Knudsen' number it is not enough. For the considered problem it corresponds to the case of the low frequencies. As shown in [8] it corresponds to a condition

$$\omega \ll \frac{\nu}{\lambda^2}.$$

Here $\nu = \eta/\rho$ is the coeffiecient of kinematic viscosity, λ is the length of free run of gas molecules.

In case of a liquid the specified parity (a sticking condition) is carried out automatically.

We consider as small parameter of the problem the quantity ε ($\varepsilon \ll 1$), which is the relation of amplitude of velocity of the wall U_0 to thermal velocity of environment $v_T = \sqrt{2k_BT/m}$, i.e. $\varepsilon = U_0/v_T$. The velocity v_T has an order of a sound velocity.

The problem (1) – (4) we will solve by the method consecutive approximations.

As a first approximation on small parameter from considered system there is the equation (1) only.

As a first approximation on small parameter the problem has isothermal and isobaric character. Concentration of gas as remains to a constant. Thus from considered system there is an equation (1) only, which in this case it will be transformed to the form

$$\frac{\partial u}{\partial t} = \nu \frac{\partial^2 u}{\partial x^2}. \tag{5}$$

Other equations in the given approximation are carried out automatically.

For the decision of the equation (5) with a boundary condition (4) we search in the form

$$u = \mathrm{Re}\,(U_0 \exp(-i\omega t + k_1 x)).$$

We obtain that

$$k_1 = \sqrt{-\frac{i\omega}{\nu}} = \sqrt{\frac{\omega}{2\nu}}(i-1) = k(i-1), \quad k = \sqrt{\frac{\omega}{2\nu}}.$$

Therefore, the solution of equation (1) is constructed

$$u = U_0 \cos(-\omega t + kx)\exp(-kx) = U_0\,\mathrm{Re}\,(e^{\xi}), \tag{6}$$

where ξ is the phase of solution $\xi = -i\omega t - kx(1-i)$.

The derivative of the soltution (6) is equal

$$\frac{\partial u}{\partial x} = \frac{U_0 k}{2}\Big[(i-1)e^{\xi} - (i+1)e^{\xi^*}\Big].$$

The derivative squared is equal

$$\left(\frac{\partial u}{\partial x}\right)^2 = \frac{U_0^2 k^2}{4}\Big[4e^{-2kx} - 2ie^{2\xi} + 2ie^{2\xi^*}\Big] =$$

$$= U_0^2 k^2\Big[e^{-2kx} - i\frac{e^{2\xi} - e^{2\xi^*}}{2}\Big]. \tag{7}$$

Thus the first summand only in the square brackets does not depend on time.

Further instead of a designation v_2 for x-component of speeds of environment in the second approximation we use the designation v, as in the first approximation this quantity is equal to zero.

Let us consider viscosity coefficient of environments to constants. In this case quantity u in the second approximation does not vary. We will notice, that this assumption not it essential to calculation of temperature jump.

Now the system (1) – (3) in the second approximation can be copied in the form

$$\rho\Big(\frac{\partial v}{\partial t} + v\frac{\partial v}{\partial x}\Big) = -\frac{\partial p}{\partial x} + \frac{\partial^2 v}{\partial x^2}\Big(\frac{4}{3}\eta + \zeta\Big), \tag{8}$$

$$\rho T\Big(\frac{\partial s}{\partial t} + v\frac{\partial s}{\partial x}\Big) = \varkappa\triangle T + \frac{\partial^2 v}{\partial x^2}\Big(\frac{4}{3}\eta + \zeta\Big) + \eta\Big(\frac{\partial u}{\partial x}\Big)^2, \tag{9}$$

and

$$\frac{\partial \rho}{\partial t} = -\frac{\partial (v\rho)}{\partial x}. \tag{10}$$

Following step to a method consecutive approximations we search for the decision of the non-uniform system of equations (8) – (10).

The structure of the partial decision of non-uniform system of the equations (8) – (10) has a following appearance, defined by the form (7) of these heterogeneities

$$v = v_\infty + v_0 e^{-2kx} + v_1 e^{2\xi} + v_1^* e^{2\xi^*},$$
$$T = T_\infty + T_0 e^{-2kx} + T_1 e^{2\xi} + T_1^* e^{2\xi^*},$$
$$\rho = \rho_\infty + \rho_0 e^{-2kx} + \rho_1 e^{2\xi} + T_1^* e^{2\xi^*}.$$

Owing to decrease of speed of environment far from a wall at once it is received, that $v_\infty = 0$. We interest the jump temperature only. This quantity does not depend on time. The contribution to it is brought only by quantities U_0, v_0, T_0, ρ_0. These quantities are constant in time. Thus $v_0 = 0$, $\mathrm{div}\mathbf{V}_0 = 0$, $p = \mathrm{const}$.

Expressions $v\frac{\partial v}{\partial x}$ and $v\frac{\partial s}{\partial x}$ have higher order малости on ε, rather than the second. In the same approximation $\varkappa$ it is possible to consider heat conductivity coefficient as constant.

As a result the system of the equations (8) – (10) is reduced to one non-trivial equation

$$\varkappa \triangle T + \eta \Big(\frac{\partial u}{\partial x}\Big)^2 = 0. \tag{11}$$

Taking into account a relation (7) from the equation (11) it is received

$$4k^2 \varkappa T_0 = -k^2 \eta U_0^2.$$

From here we find T_0

$$T_0 = -\eta U_0^2 / 4\varkappa.$$

Let us designate surface temperature through T_s. It is obvious, that

$$T_s = T_\infty + T_0.$$

From here follows, that a difference of temperatures between temperature of a surface and in temperature far from a wall, (i.e. temperature jump δT) it is equal

$$\delta T = T_\infty - T_s = \frac{\eta U_0^2}{4\varkappa}. \tag{12}$$

Let us notice, that the received expression (12) did not include coefficient of the second viscosity ζ. Temperature jump is proportional to coefficient of dynamic viscosity, square of amplitude of speed of a wall, and it is inverse proportional to the coefficient of heat conductivity.

The received result is fair both for gas, and for the liquid environment.

Thus, generating of shift waves in the viscous environment by oscillation surface leads to occurrence of jump of temperature (12) which comes to light as the result of nonlinear analysis.

Let us notice, that the first researches of jump of temperature in the rarefied gas were spent in the end of XIX century [15].

REFERENCES

[1] *Stokes G.G.* On the effect of internal friction of fluids on the motion of pendulums. Trans. Cambr. Phil. IX. 1851. P. 8–106.

[2] *Ai L., Vafai K.* An Investigation of Stokes' Second Problem for Non-Newtonian Fluids //Numerical Heat Transfer, Part A: Applications, V. 47. 2005. P. 955 - 980.

[3] *Khan M., Asia A., Fetecau C.* On exact solutions of Stokes second problem for a Burgers' fluid, I. The case $\gamma < \lambda^2/4$. // J. Appl. Math. and Phys. (ZAMP). 2009. V. 61. №4. P. 697-720.

[4] *Steinhell E., Scherber W., Seide M., Rieger H.* Investigation on the interaction of gases and well defined solid surfaces with respect to possibilities for reduction of aerodynamic friction and aerothermal heating // Rarefied gas dynamics. Ed. J.L. Potter. N.Y.: Acad. press. 1977. P. 589-602.

[5] *Graebel W.P.* Engineering Fluid Mechanics. New York. Taylor & Francis. 2001. 752 p.

[6] *Cleland A.N., Roukes M.L.* A nanometre–scale mechanical electrometer // Nature. Vol. 392. 1998. P. 160-162.

[7] *Karabacak D.M., Yakhot V., and Ekinci K.L.* High–Frequency Nanofluidics: An Experimental Study using Nanomechanical Resonators, Phys. Rev. Lett. 98. 2007. PP 254505.

[8] *Sharipov F. and Kalempa D.* Gas flow around a longitudinally oscillating plate at arbitrary ratio of collision frequency to oscillation frequency// Rarefied Gas Dynamics: 25-th International Symposium, edited by M.S. Ivanov and A.K. Rebrov. Novosibirsk, 2007. P. 1140-1145.

[9] *Dudko V. V., Yushkanov A. A., Yalamov Yu. I.* Influence of properties of surfaces on characteristics of shift waves // J. of Technical Ptysics. 2005. V. 75. Issue 4. P. 134-135. [russian]

[10] *Dudko V. V., Yushkanov A. A., Yalamov Yu. I.* Generation of shear waves in gas by a vibrating surface// High Temperature, April 2009, Volume 47, Issue 2, pp 243-249.

[11] *Akimova V.A., Latyshev A.V., Yushkanov A.A.* Analytical Solution of Stokes' Second Problem on the Behavior of Rarefies Gas over Oscillating Surface// Fluid Dynamics, 2013, Vol. 48, No. 1, pp. 109-122.

[12] *Latyshev A.V., Yushkanov A.A.* Analytical Solution of the Second Stokes Problem for Rarefied Gas with Cercignani Boundary Conditions// Comp. Math. and Math. Phys., 2013, Vol. 53, No. 3, pp. 336-349.

[13] *Choudhary M.K., Choudhary S. Sharma R.* Unsteady MHD flow and heat transfer over a stretching permeable surface with suction or injection//Procedia Engineering. 2015. V. **127**. P. 703-710.

[14] Fluid mechanics by L.D. Landau and E.M. Lifshitz ; translated from the Russian by J.B. Sykes and W.H. Reid. [electronic resource] - 2nd ed., 2nd English ed., rev. Oxford, England Pergamon Press - Course of theoretical physics ; xiii, 539 p.

[15] *Smoluchowski M.* Über Wärmeleitung in verdünten Gasen// Ann. Phys. Chem. 1898. B. 64. S. 101–130.